



## Contents

Section	Title	Page
<b>1</b>	<b>Plain Track</b>	
1.1	Recommended Minimum Curvature	2-1-2
1.2	Transition Curves and Superelevation	2-1-2
1.2.1	Introduction	2-1-2
1.2.2	Setting out transition curves	2-1-3
1.3	Double Track Clearances	2-1-4
1.3.1	Graphical solution	2-1-5
1.3.2	Calculated solution	2-1-5
1.4	Prototype Rail Sections	2-1-6
1.5	Track Making	2-1-7
1.5.1	Track making jig	2-1-7
1.5.2	Track making jig in use	2-1-8
	<b>Data Sheets</b>	
D2.1.1	Track Dimensions	
	Dimensions of prototype rail sections	D2.1.1.1
	Crossing dimensions compatible with pre-BRMSB wheelsets	D2.1.1.5
D2.1.2	Clearance Required on Curves	
<b>2</b>	<b>Pointwork</b>	
2.1	Development of the Prototype	2-2-1
2.1.1	Historical background	2-2-1
2.1.2	Switches	2-2-2
2.1.3	Switch chairs	2-2-4
2.1.4	Crossings	2-2-5
2.1.5	Terminology; names of components	2-2-5
2.1.6	Variety of prototype pointwork	2-2-6
2.1.7	Refinement of the design of pointwork	2-2-6
2.1.8	Material to be found in typical British station layouts	2-2-8
2.2	Pointwork Configurations	2-2-9
2.2.1	Single turnouts	2-2-9
2.2.2	Tandem or double turnout	2-2-9
2.2.3	Three-throw turnout	2-2-10
2.2.4	Four throw turnout	2-2-11
2.2.5	Five throw turnout	2-2-12
2.2.6	Obtuse crossings	2-2-12
2.2.7	Square crossings	2-2-13
2.2.8	Switch diamonds	2-2-13
2.2.9	Swing nose crossing	2-2-14
2.2.10	Spring crossings	2-2-15
2.2.11	Double junctions	2-2-15
2.2.12	Inside slip points	2-2-15
2.2.13	Outside slip points	2-2-17
2.2.14	Scissors crossovers	2-2-18
2.2.15	Trap points	2-2-19
2.2.16	Catch points	2-2-19
2.2.17	Interlaced or gauntlet track	2-2-20
2.2.18	Gauntlet or interlaced turnouts	2-2-21
2.2.19	Multi-gauge track	2-2-21
2.3	Model Pointwork	2-2-23
2.3.1	Model switches	2-2-23
2.3.2	Dimensional compromises	2-2-23

2.4	Basic Turnout Construction	2-2-25
2.4.1	Equipment	2-2-25
2.4.2	Preparation for assembly	2-2-25
2.4.3	Assembly sequence - copper clad sleepers	2-2-26
2.4.4	Assembly sequence - chaired track	2-2-28
2.4.5	Assembly sequence - riveted track	2-2-30
2.5	Custom Pointwork Drawings	2-2-31
2.5.1	Making drawings using templates	2-2-32
2.5.1.1	Straight switches	2-2-32
2.5.1.2	Semi-curved switches	2-2-34
2.5.1.3	Fully curved switches	2-2-34
2.5.2	Making drawings using offsets	2-2-34
2.5.2.1	Drawing a curved or semi-curved switch	2-2-35
2.5.2.2	Drawing the turnout curve	2-2-37
2.5.2.3	Drawing the crossing	2-2-37
2.5.3	Turnouts on curves	2-2-37
2.5.3.1	Using offsets	2-2-37
2.5.4	Three-way turnouts	2-2-39
2.5.5	Timbering	2-2-39
2.5.6	Stretcher bars	2-2-40
2.5.7	Check rails	2-2-40
2.6	Making Pointwork Components	2-2-41
2.6.1	Blades and stock rails	2-2-41
2.6.1.1	Making the blades	2-2-42
2.6.1.2	Notes on filing blades	2-2-44
2.6.2	Stock rails	2-2-45
2.6.3	Common crossings	2-2-46
2.6.3.1	Point and splice rails	2-2-46
2.6.3.2	Wing and check rails	2-2-47
2.6.4	Obtuse crossings	2-2-48
2.6.5	Moving the blades	2-2-48
2.6.5.1	Stretcher bars	2-2-48
2.6.5.2	Under baseboard drive unit	2-2-50
2.6.5.3	Pivoting straight switches	2-2-50
2.6.6	Other details	2-2-53
2.7	Universal Turnouts	2-2-55
2.7.1	'Tinplate' turnouts	2-2-55
2.7.2	Swing nose crossings	2-2-56

## Data Sheets

<b>D2.2.1 Turnout Geometry</b>		
	Turnout Geometry	D2.2.1.1
	Turnout Geometry - Calculations	D2.2.1.2
<b>D2.2.2 Switches</b>		
	Straight Switches (All Standards)	D2.2.2.1
	Semi-curved Switches (All Standards)	D2.2.2.2
	Fully Curved Switches (All Standards)	D2.2.2.3
<b>D2.2.3 Turnout Curve Tables</b>		
	Turnout Curve Tables for Scaleseven Standard	D2.2.3.1
	Turnout Curve Tables for 0 Fine Standard	D2.2.3.2
	Turnout Curve Tables for 0 Coarse Standard (*)	D2.2.3.3
	Turnout Curve Tables for 0 Coarse Standard (**)	D2.2.3.4
<b>D2.2.4 Common Crossing (All Standards)</b>		
<b>D2.2.5 Obtuse Crossing (All Standards)</b>		
<b>D2.2.6 Timbering</b>		



<b>3</b>	<b>Electrified track - Overhead Construction (In preparation)</b>	
<b>4</b>	<b>Electrified track - Third and Fourth Rail Construction (In preparation)</b>	
<b>5</b>	<b>Causes of Derailments</b>	
5.1	Introduction	2-5-1
5.2	Track Defects	2-5-1
5.2.1	Plain Track	2-5-1
5.2.2	Pointwork	2-5-2
5.3	Vehicle Defects	2-5-3
5.3.1	Wheelsets dimensionally incorrect	2-5-3
5.3.2	Axle alignment	2-5-3
5.3.3	Bogie freedom	2-5-3
5.3.4	Light weight	2-5-3
5.3.5	Excessive side play	2-5-3
5.3.6	Wheel profile	2-5-3
5.3.7	Journal friction	2-5-4
5.3.8	Bufferlocking	2-5-4
5.3.9	Coupling links or chains fouling the track	2-5-4